

ContiEcoContact™ 3

Diámetro de rin	Serie	Ranflap	Protector de rin	Equipo original	Medida	Índice de carga	Índice de velocidad	Rango de carga	Costado	Diámetro total (cm.)	Prof de piso	Ancho rin recomendado		
13	80				145/80R13	75	T	SL	CN	56.22	8	4		
					165/80R13	83	T	SL	CN	59.42	8	4.5		
		70			OE	145/70R13	71	T	SL	CN	53.32	8	4.5	
						155/70R13	75	T	SL	CN	54.72	8	4.5	
					155/70R13	75	T	SL	CN	54.72	8	4.5		
					OE	155/70R13	75	T	SL	CN	54.72	8	4.5	
				OE	155/70R13	75	T	SL	CN	54.72	8	4.5		
					165/70R13	79	T	SL	CN	56.12	8	5		
	65					165/70R13 XL	83	T	XL	CN	56.12	8	5	
						175/70R13	82	T	SL	CN	57.52	8	5	
						185/70R13	86	T	SL	CN	58.92	8	5.5	
						165/65R13	77	T	SL	CN	54.47	8	5	
				OE	175/65R13	80	T	SL	CN	55.77	8	5		
14	80				175/80R14	88	T	SL	CN	63.56	8	5		
					175/80R14	88	H	SL	CN	63.56	8	5		
		70			OE	165/70R14	81	T	SL	CN	58.66	8	5	
					OE	165/70R14	81	T	SL	CN	58.66	8	5	
					OE	165/70R14	81	T	SL	CN	58.66	8	5	
						175/70R14	84	T	SL	CN	60.06	8	5	
					185/70R14	88	T	SL	CN	61.46	8	5.5		
				OE	185/70R14	88	T	SL	CN	61.46	8	5.5		
	65					185/70R14	88	H	SL	CN	61.46	8	5.5	
					OE	155/65R14	75	T	SL	CN	55.71	8	4.5	
			FR		OE	155/65R14	75	T	SL	CN	55.71	8	4.5	
					OE	155/65R14	75	T	SL	CN	55.71	8	4.5	
					OE	165/65R14	79	T	SL	CN	57.01	8	4.5	
					OE	165/65R14	79	T	SL	CN	57.01	8	4.5	
						175/65R14	82	T	SL	CN	58.31	8	5	
					OE	175/65R14	82	T	SL	CN	58.31	8	5	
						175/65R14	82	T	SL	CN	58.31	8	5	
					OE	175/65R14	82	T	SL	CN	58.31	8	5	
					OE	175/65R14	82	T	SL	CN	58.31	8	5	
						185/65R14	86	T	SL	CN	59.61	8	5.5	
	60					185/65R14	86	T	SL	CN	59.61	8	5.5	
					OE	175/65R14	82	H	SL	CN	58.31	8	5	
					OE	185/65R14	86	H	SL	CN	59.61	8	5.5	
						165/60R14	75	T	SL	CN	55.36	8	4.5	
					165/60R14 XL	79	T	XL	CN	55.36	8	4.5		
					185/60R14	82	T	SL	CN	57.76	8	5.5		
				OE	185/60R14	82	T	SL	CN	57.76	8	5.5		
				OE	165/60R14	75	H	SL	CN	55.36	8	5		
					185/60R14	82	H	SL	CN	57.76	8	5.5		
					185/60R14	82	H	SL	CN	57.76	8	5.5		
15		65				OE	165/65R15	81	T	SL	CN	59.55	8	5
					OE	165/65R15	81	T	SL	CN	59.55	8	5	
					OE	175/65R15	84	T	SL	CN	60.85	8	5	
					OE	175/65R15	84	T	SL	CN	60.85	8	5	
					OE	185/65R15	88	T	SL	CN	62.15	8	5.5	
						185/65R15	88	T	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	T	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	T	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	T	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	H	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	H	SL	CN	62.15	8	5.5	
					OE	185/65R15	88	H	SL	CN	62.15	8	5.5	
	60					OE	195/65R15	91	T	SL	CN	63.45	8	6
						OE	195/65R15	91	T	SL	CN	63.45	8	6
						OE	195/65R15	91	T	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
						OE	195/65R15	91	H	SL	CN	63.45	8	6
55	FR				OE	155/60R15	74	T	SL	CN	56.7	8	4.5	
					OE	175/60R15	81	H	SL	CN	59.1	8	5	
				OE	175/55R15	77	T	SL	CN	57.35	8	5.5		

Medidas

Beneficios



Índice de velocidad

T= hasta 190 km/h

H= hasta 210 km/h

UTQG <165

Treadwear 240

Traction A

Temperature A

UTQG >175

Treadwear 300

Traction A

Temperature A

CN= Costado negro

Índice de carga

SL= Carga standard

XL= Carga extra

OE= Equipo original

FR= Protector de rin