

# ContiTouringContact CT/CH/CV/CW 95

Díámetro de rín	Serie	Runtflat	Protector de rín	Equipo original	Medida	Índice de carga	Índice de velocidad	Rango de carga	Costado	Díámetro total (cm.)	Prof. de piso	Ancho rín recomendado					
15	65			OE	175/65R15	84	H	SL	CN	60.85	8	5					
					215/60R15	93	H	SL	CN	63.9	8	6.5					
					225/60R15	96	H	SL	CN	65.1	8	7					
16	65			OE	205/65R16	94	T	SL	CN	67.29	8	6					
					235/60R16	100	H	SL	CN	68.84	8	7					
					235/60R16	100	H	SL	CN	68.84	8	7					
	55				OE	235/60R16	100	H	SL	CN	68.84	8	7				
						205/55R16	91	V	SL	CN	63.19	8	6.5				
						225/55R16	95	H	SL	CN	65.39	8	7				
						225/55R16	95	H	SL	CN	65.39	8	7				
50			FR	OE	225/55R16	95	V	SL	CN	65.39	8	7					
					225/55R16	94	V	SL	CN	65.39	8	7					
					225/50R16	92	H	SL	CN	63.14	8	7					
					17	65			OE	215/65R17	98	T	SL	CN	71.13	8	6.5
										215/65R17	98	T	SL	CN	71.13	8	6.5
215/65R17	98	T	SL	CN						71.13	8	6.5					
60				OE	215/60R17	95	T	SL	CN	68.98	8	6.5					
					225/55R17	97	H	SL	CN	67.93	8	7					
55				OE	225/55R17	95	V	SL	CN	67.93	8	7					
					205/50R17 XL	93	V	XL	CN	63.68	8	6.5					
					225/50R17	94	V	SL	CN	65.68	8	7					
45				FR	225/45R17	91	H	SL	CN	63.43	8	7.5					
					245/45R17	95	H	SL	CN	65.23	8	8					
18	60			OE	225/60R18	99	H	SL	CN	72.72	8	6.5					
					225/60R18	99	H	SL	CN	72.72	8	6.5					
					225/60R18	99	H	SL	CN	72.72	8	6.5					
					225/60R18	99	H	SL	CN	72.72	8	6.5					
					225/60R18	99	H	SL	CN	72.72	8	6.5					
					235/50R18	97	H	SL	CN	69.22	8	7.5					
					255/45R18	99	H	SL	CN	68.67	8	8.5					
40	FR	OE	225/40R18 XL	92	W	XL	CN	63.72	8	8							
19	35	FR	OE	255/35R19	92	W	SL	CN	66.11	8	9						

## Medidas

Beneficios



### Índice de velocidad

T= hasta 190 km/h  
 H= hasta 210 km/h  
 V= hasta 240 km/h  
 W= hasta 270 km/h  
 Y= hasta 300 km/h

### UTQG

Treadwear 360  
 Traction A  
 Temperature A

CN= Costado negro

### Índice de carga

SL= Carga standard  
 XL= Carga extra

OE= Equipo original  
 FR= Protector de rín