

If you'd like to print this page please set your print settings to landscape.



Product Code	Tire Size	Service Desc.	Construction	Sidewall	UTQG	Rim Width Range (inch)	Section Width on Measured Rim Width (inch)	Overall Dia (inch)	Tire Weight (lbs.)	Static Load Radius (inch)	RPM	Tread Depth (1/32")	Max Load Single (lbs)	Max Load Dual (lbs)	Max Inflation (psi)
1899813	P175/70R13	82T	-	BSW	640 A/B	4.5 - 6.0	7.0 on 5.0	22.7	14.6	8.8	916	10.0	1034	-	44
1906313	P185/70R13	85T	-	BSW	640 A/B	4.5 - 6.0	7.4 on 5.5	23.2	15.4	9.1	894	10.0	1133	-	44
1905813	P155/80R13	79T	-	WSW	640 A/B	4.0 - 5.0	6.2 on 4.5	22.8	13.5	8.8	922	10.0	957	-	44
1899913	P185/60R14	82T	-	BSW	640 A/B	5.0 - 6.5	7.4 on 5.5	22.8	15.3	8.9	913	10.0	1045	-	44
1901013	P195/60R14	85T	-	BSW	640 A/B	5.5 - 7.0	7.9 on 6.0	23.2	17.5	9.1	894	10.0	1133	-	44
1906013	P175/65R14	81T	-	BSW	640 A/B	5.0 - 6.0	7.0 on 5.0	23.0	15.4	9.0	904	10.0	1016	-	44
1900013	P185/65R14	85T	-	BSW	640 A/B	5.0 - 6.5	7.4 on 5.5	23.5	17.0	9.2	885	10.0	1122	-	44
1906613	P195/65R14	88T	-	BSW	640 A/B	5.5 - 7.0	7.9 on 6.0	24.0	17.9	9.4	865	10.0	1232	-	44
1906413	P185/70R14	87T	-	BSW	640 A/B	4.5 - 6.0	7.4 on 5.5	24.2	16.4	9.5	857	10.0	1199	-	44
1906713	P195/70R14	90T	-	BSW	640 A/B	5.0 - 6.5	7.9 on 6.0	24.8	17.8	9.7	838	10.0	1309	-	44
1900713	P205/70R14	95T	-	BSW	640 A/B	5.0 - 7.0	8.2 on 6.0	25.4	19.4	9.9	819	10.0	1521	-	44
1900813	P215/70R14	96T	-	BSW	640 A/B	5.5 - 7.0	8.7 on 6.5	25.9	21.2	10.1	802	10.0	1554	-	44
1906513	P185/75R14	89T	-	WSW	640 A/B	4.5 - 6.0	7.2 on 5.0	25.0	17.6	9.7	832	10.0	1287	-	44
2104303	P185/75R14	89T	-	BSW	640 A/B	4.5 - 6.0	7.2 on 5.0	25.0	17.4	9.7	832	10.0	1287	-	44
1906813	P195/75R14	92T	-	WSW	640 A/B	5.0 - 6.5	7.7 on 5.5	25.5	19.2	9.9	814	10.0	1518	-	44
2104323	P195/75R14	92T	-	BSW	640 A/B	5.0 - 6.5	7.7 on 5.5	25.5	18.7	9.9	814	10.0	1518	-	44
1907313	P205/75R14	95T	-	WSW	640 A/B	5.0 - 7.0	8.0 on 5.5	26.1	20.4	10.2	795	10.0	1529	-	44
2104343	P205/75R14	95T	-	BSW	640 A/B	5.0 - 7.0	8.0 on 5.5	26.1	20.5	10.2	795	10.0	1529	-	44
1900213	P195/60R15	87T	-	BSW	680 A/B	5.5 - 7.0	7.9 on 6.0	24.2	18.7	9.4	858	10.0	1188	-	44
1900413	P205/60R15	90T	-	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	24.7	19.9	9.6	842	10.0	1298	-	44
1907513	P215/60R15	93T	-	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	25.2	22.5	9.8	826	10.0	1408	-	44
1908113	P225/60R15	95T	-	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	25.6	23.3	10.0	811	10.0	1518	-	44
1900113	P185/65R15	86T	-	BSW	680 A/B	5.0 - 6.5	7.4 on 5.5	24.5	17.7	9.5	850	10.0	1168	-	44
1900313	P195/65R15	89T	-	BSW	680 A/B	5.5 - 7.0	7.9 on 6.0	25.0	19.2	9.8	830	10.0	1276	-	44
1900613	P205/65R15	92T	-	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	25.5	20.7	9.9	818	10.0	1397	-	44
1907613	P215/65R15	95T	-	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.0	23.4	10.1	798	10.0	1507	-	44
1907213	P205/70R15	95T	-	WSW	680 A/B	5.0 - 7.0	8.2 on 6.0	26.3	21.5	10.3	789	10.0	1496	-	44
2104243	P205/70R15	95T	-	BSW	680	5.0 - 7.0	8.2 on 6.0	26.3	20.4	10.3	798	10.0	1496	-	44

2104303	P205/70R15	97T	-	BSW	A/B	6.0 - 7.0	8.2 on 6.5	26.3	26.4	10.5	773	10.0	1470	-	44
1907813	P215/70R15	97T	-	WSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.8	23.5	10.5	773	10.0	1617	-	44
2104483	P215/70R15	97T	-	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.8	23.3	10.5	773	10.0	1617	-	44
1908313	P225/70R15	100T	-	BSW	680 A/B	6.0 - 7.5	9.0 on 6.5	27.4	25.4	10.7	757	10.0	1749	-	44
1908913	P235/70R15	102T	-	BSW	680 A/B	6.0 - 8.0	9.4 on 7.0	28.0	26.9	10.9	742	10.0	1896	-	44
1907413	P205/75R15	97T	-	WSW	680 A/B	5.0 - 7.0	8.0 on 5.5	27.1	22.0	10.6	766	10.0	1595	-	44
2104383	P205/75R15	97T	-	BSW	680 A/B	5.0 - 7.0	8.0 on 5.5	27.1	21.6	10.6	766	10.0	1595	-	44
1908013	P215/75R15	100T	-	WSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.7	24.2	10.8	751	10.0	1738	-	44
2104403	P215/75R15	100T	-	BSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.7	23.8	10.8	751	10.0	1738	-	44
1908513	P225/75R15	102T	-	WSW	680 A/B	6.0 - 7.5	8.8 on 6.0	28.3	25.8	11.0	734	10.0	1870	-	44
2104423	P225/75R15	102T	-	BSW	680 A/B	6.0 - 7.5	8.8 on 6.0	28.3	25.7	11.0	734	10.0	1870	-	44
1909113	P235/75R15	105T	-	WSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.5	11.1	720	10.0	2028	-	44
2104443	P235/75R15	105T	-	BSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.6	11.1	720	10.0	2028	-	44
1909213	P235/75R15	108T	XL	WSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	27.7	11.1	720	10.0	2183	-	44
2104463	P235/75R15	108T	XL	BSW	680 A/B	6.0 - 8.0	9.2 on 6.5	28.9	29.9	11.1	720	10.0	2183	-	44
1906913	P205/55R16	89T	-	BSW	680 A/B	5.5 - 7.5	8.4 on 6.5	24.9	21.1	9.7	835	10.0	1276	-	44
1900513	P205/60R16	91T	-	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	25.7	21.3	10.0	812	10.0	1353	-	44
1909313	P215/60R16	94T	-	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	26.1	24.3	10.2	795	10.0	1474	-	44
1900913	P225/60R16	97T	-	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	26.6	25.3	10.4	781	10.0	1606	-	44
1908613	P235/60R16	99T	-	BSW	680 A/B	6.5 - 8.5	9.4 on 7.0	27.1	27.4	10.6	767	10.0	1705	-	44
1907113	P205/65R16	94T	-	BSW	680 A/B	5.5 - 7.5	8.2 on 6.0	26.5	21.6	10.3	785	10.0	1474	-	44
1907713	P215/65R16	96T	-	BSW	680 A/B	6.0 - 7.5	8.7 on 6.5	27.0	25.2	10.5	769	10.0	1518	-	44
2100573	P235/65R16	103T	-	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	29.0	28.8	13.0	716	10.0	1929	-	44
1907913	P215/70R16	99T	-	BSW	680 A/B	5.5 - 7.0	8.7 on 6.5	27.8	25.2	17.2	747	10.0	1705	-	44
1908413	P225/70R16	101T	-	BSW	680 A/B	6.0 - 7.5	9.0 on 6.5	28.7	26.8	17.9	724	10.0	1819	-	44
1909013	P235/70R16	104T	-	BSW	680 A/B	6.0 - 8.0	9.5 on 7.0	29.2	28.5	18.3	711	10.0	1984	-	44
1908213	P225/60R17	98T	-	BSW	680 A/B	6.0 - 8.0	9.0 on 6.5	27.6	27.3	12.6	753	10.0	1649	-	44
2100473	P235/60R17	100T	-	BSW	680 A/B	6.5 - 8.5	9.4 on 7.0	28.1	28.9	12.8	739	10.0	1764	-	44
1908713	P235/65R17	103T	-	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	29.0	30.1	13.2	716	10.0	1929	-	44
1908813	P235/65R18	104T	-	BSW	680 A/B	6.5 - 8.5	9.5 on 7.0	30.0	32.0	13.2	692	10.0	1984	-	44