

If you'd like to print this page please set your print settings to landscape.



Product Code	Tire Size	Service Desc.	Construction	Sidewall	UTQG	Rim Width Range (inch)	Section Width on Measured Rim Width (inch)	Overall Dia (inch)	Tire Weight (lbs.)	Static Load Radius (inch)	RPM	Tread Depth (1/32")	Max Load Single (lbs)	Max Load Dual (lbs)	Max Inflation (psi)
1770213	P185/60R14	82H	-	BSW	440 AA/A	5.0 - 6.5	7.4 on 5.5	22.8	16.0	8.9	913	10.0	1047	-	44
1775413	P195/60R14	85H	-	BSW	440 AA/A	5.5 - 7.0	7.9 on 6.0	23.2	17.5	9.1	894	10.0	1135	-	44
1729913	P185/65R14	85H	-	BSW	440 AA/A	5.0 - 6.5	7.3 on 6.0	23.4	16.5	10.7	888	10.0	1124	-	44
2005353	P195/55R15	84V	-	BSW	440 AA/A	5.5 - 7.0	7.9 on 6.0	23.4	19.1	10.7	888	10.0	1102	-	44
1770313	P195/60R15	87H	-	BSW	440 AA/A	5.5 - 7.0	7.9 on 6.0	24.2	18.2	9.4	858	10.0	1190	-	44
1774713	P205/60R15	90H	-	BSW	440 AA/A	5.5 - 7.5	8.2 on 6.0	24.7	19.9	9.6	842	10.0	1323	-	44
1774813	P215/60R15	93H	-	BSW	440 AA/A	6.0 - 7.5	8.7 on 6.5	25.2	23.6	9.8	826	10.0	1411	-	44
1799413	P185/65R15	86H	-	BSW	440 AA/A	5.0 - 6.5	7.4 on 5.5	24.5	18.6	9.5	850	10.0	1168	-	44
1755913	P195/65R15	89H	-	BSW	440 AA/A	5.5 - 7.0	7.9 on 6.0	25.0	19.3	9.8	830	10.0	1279	-	44
1756313	P205/65R15	94H	-	BSW	440 AA/A	5.5 - 7.5	8.2 on 6.0	25.5	20.7	9.9	818	10.0	1477	-	44
1770413	P215/65R15	95H	-	BSW	440 AA/A	6.0 - 7.5	8.7 on 6.5	26.0	24.2	10.1	798	10.0	1510	-	44
2100663	P205/50R16	86H	-	BSW	440 A/A	5.5 - 7.5	8.4 on 7.5	24.1	20.1	14.0	862	10.0	1168	0	44
2102073	P195/55R16	86V	-	BSW	440 AA/A	5.0 - 7.0	7.9 on 6.0	24.4	19.7	11.3	851	10.0	1168	0	44
1756213	P205/55R16	89H	-	BSW	440 AA/A	5.5 - 7.5	8.4 on 6.5	24.9	19.9	9.7	835	10.0	1279	-	44
1782113	P215/55R16	91H	-	BSW	440 AA/A	6.0 - 7.5	8.9 on 7.0	25.3	22.8	9.9	822	10.0	1356	-	44
1768013	P225/55R16	94H	-	BSW	440 AA/A	6.0 - 8.0	9.2 on 7.0	25.8	25.2	10.0	807	10.0	1477	-	44
1770513	P235/55R16	98H	-	BSW	440 AA/A	6.5 - 8.5	9.6 on 7.5	26.1	26.3	10.2	795	10.0	1565	-	44
1745613	P205/60R16	91H	-	BSW	440 AA/A	5.5 - 7.5	8.1 on 6.0	25.7	21.1	10.0	808	10.0	1356	-	44
1767913	P215/60R16	94H	-	BSW	440 AA/A	6.0 - 7.5	8.7 on 6.5	26.1	23.8	10.2	795	10.0	1477	-	44
2100403	P225/60R16	97H	-	BSW	440 AA/A	6.0 - 8.0	9.0 on 6.5	26.6	24.4	10.4	781	10.0	1609	-	44
1774913	P235/60R16	99H	-	BSW	440 AA/A	6.5 - 8.5	9.4 on 7.0	27.1	26.4	10.6	767	10.0	1709	-	44
1725913	P205/65R16	94H	-	BSW	440 AA/A	5.5 - 7.5	8.2 on 6.0	26.5	22.9	10.3	785	10.0	1477	-	44
1799613	P215/65R16	96H	-	BSW	440 AA/A	6.0 - 7.5	8.7 on 6.5	27.0	24.6	10.5	769	10.0	1565	-	44
2103863	P215/45R17	87H	-	BSW	440 A/A	7.0 - 8.0	8.4 on 7.0	24.7	20.6	14.5	841	10.0	1202	0	44
2102093	205/50R17	93V	RF	BSW	440 A/A	5.5 - 7.5	8.4 on 6.5	25.1	22.3	9.8	827	10.0	1433	0	50
1756413	P215/50R17	93H	-	BSW	440 A/A	6.0 - 7.5	8.9 on 7.0	25.5	22.8	9.9	814	10.0	1433	-	44
1775013	P225/50R17	93V	-	BSW	440 A/A	6.0 - 8.0	9.2 on 7.0	25.9	23.9	10.1	802	10.0	1433	-	44