



Primacy MXV4



Performance Category:
[Grand Touring All-Season](#)

ALL OTHER SIZES FOR THIS TIRE

| Size Service Description Load Range | UTQG | Max Load | Max. Inflation Press. | Tread Depth | Tire Weight | Rim Width Range | Meas. Rim Width | Sect. Width | Tread Width | Overall Diam. | Revs Per Mile | Country of Origin* |
|---|------------------|-------------|-----------------------------|----------------|----------------|-----------------------|-----------------------|----------------|----------------|------------------|---------------------|-----------------------|
| 185/65R15 88H SL | 620 A A ----- | 1235 lbs. | 44 psi | 11/32" | 20 lbs. | 5-6.5" | 5.5" | 7.4" | NA | 24.4" | 851 | US --- |
| 195/60R15 88H SL | 620 A A ----- | 1235 lbs. | 44 psi | 11/32" | 22 lbs. | 5.5-7" | 6" | 7.9" | NA | 24.2" | 862 | US --- |
| 195/60R15 88V SL | 620 A A ----- | 1235 lbs. | 44 psi | 11/32" | 22 lbs. | 5.5-7" | 6" | 7.9" | NA | 24.2" | 862 | US --- |
| 195/65R15 91H SL | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 23 lbs. | 5.5-7" | 6" | 7.9" | NA | 25" | 834 | US --- |
| 205/60R15 91H SL | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 23 lbs. | 5.5-7.5" | 6" | 8.2" | NA | 24.7" | 844 | US --- |
| 205/65R15 94H SL | 620 A A ----- | 1477 lbs. | 44 psi | 11/32" | 22 lbs. | 5.5-7.5" | 6" | 8.2" | 5.2" | 25.5" | 814 | CA --- |
| 205/65R15 94V SL | 620 A A ----- | 1477 lbs. | 44 psi | 11/32" | 22 lbs. | 5.5-7.5" | 6" | 8.2" | NA | 25.5" | 814 | CA --- |
| 215/60R15 94H SL | 620 A A ----- | 1477 lbs. | 44 psi | 11/32" | 27 lbs. | 6-7.5" | 6.5" | 8.7" | NA | 25.2" | 827 | RO --- |
| 225/60R15 96H SL | 620 A A ----- | 1565 lbs. | 44 psi | 11/32" | 25 lbs. | 6-8" | 6.5" | 9" | NA | 25.6" | 811 | US --- |
| 205/55R16 91H SL | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 23 lbs. | 5.5-7.5" | 6.5" | 8.4" | NA | 24.9" | 837 | US --- |
| 205/55R16 91V SL | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 23 lbs. | 5.5-7.5" | 6.5" | 8.4" | NA | 24.9" | 837 | US , CA ---, --- |
| 205/60R16 92H SL | 620 A A ----- | 1389 lbs. | 44 psi | 11/32" | 24 lbs. | 5.5-7.5" | 6" | 8.2" | NA | 25.7" | 808 | US , CA ---, --- |
| 205/60R16 92V SL | 620 A A ----- | 1389 lbs. | 44 psi | 11/32" | 24 lbs. | 5.5-7.5" | 6" | 8.2" | NA | 25.7" | 808 | US , CA ---, --- |
| 205/65R16 95H SL | 620 A A ----- | 1521 lbs. | 44 psi | 11/32" | 25 lbs. | 5.5-7.5" | 6" | 8.2" | NA | 26.5" | 786 | RO --- |
| 215/55R16 93H SL | 620 A A ----- | 1433 lbs. | 44 psi | 11/32" | 24 lbs. | 6-7.5" | 7" | 8.9" | NA | 25.3" | 820 | US --- |
| 215/55R16 93V SL | 620 A A ----- | 1435 lbs. | 44 psi | 11/32" | 25 lbs. | 6-7.5" | 7" | 8.9" | NA | 25.3" | 820 | US --- |
| 215/60R16 94H SL Green X | 500 A A ----- | 1477 lbs. | 44 psi | | 23 lbs. | 6-7.5" | 6.5" | 8.7" | NA | 26.1" | 797 | CA --- |
| 225/60R16 98H SL | 620 A A ----- | 1653 lbs. | 44 psi | 11/32" | 26 lbs. | 6-8" | 6.5" | 9" | NA | 26.6" | 783 | US --- |

28/12/2009

Tire Specs for Michelin Primacy MXV4

| | | | | | | | | | | | | |
|--|------------------|-------------|-----------------------------|----------------|----------------|-----------------------|-----------------------|----------------|----------------|------------------|---------------------|-----------------------|
| 225/60R16 98V SL ----- | 620 A A ----- | 1653 lbs. | 44 psi | 11/32" | 26 lbs. | 6-8" | 6.5" | 9" | NA | 26.6" | 783 | US --- |
| 225/65R16 100H SL ----- | 620 A A ----- | 1764 lbs. | 44 psi | 11/32" | 27 lbs. | 6-8" | 6.5" | 9" | NA | 27.5" | 758 | US --- |
| 235/60R16 100H SL ----- | 620 A A ----- | 1764 lbs. | 44 psi | 11/32" | 28 lbs. | 6.5-8.5" | 7" | 9.4" | NA | 27.1" | 769 | US --- |
| 215/50R17 91H SL ----- | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 24 lbs. | 6-7.5" | 7" | 8.9" | NA | 25.5" | 814 | US --- |
| 215/50R17 91V SL ----- | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 23 lbs. | 6-7.5" | 7" | 8.9" | NA | 25.5" | 814 | US --- |
| 215/50R17 95V XL ----- | 620 A A ----- | 1521 lbs. | 50 psi | | 23 lbs. | 6-7.5" | 7" | | | | | US --- |
| 215/55R17 94H SL ----- | 620 A A ----- | 1477 lbs. | 44 psi | 11/32" | 25 lbs. | 6-7.5" | 7" | 8.9" | NA | 26.3" | 792 | US --- |
| 225/45R17 91H SL ----- | 620 A A ----- | 1356 lbs. | 44 psi | 11/32" | 24 lbs. | 7-8.5" | 7.5" | 8.9" | NA | 25" | 834 | US --- |
| 225/55R17 97H SL ----- | 620 A A ----- | 1609 lbs. | 44 psi | 11/32" | 26 lbs. | 6-8" | 7" | 9.2" | NA | 26.8" | 778 | US --- |
| 225/55R17 97V SL ----- | 620 A A ----- | 1609 lbs. | 44 psi | 11/32" | 26 lbs. | 6-8" | 7" | 9.2" | NA | 26.8" | 778 | US --- |
| 235/55R17 99H SL ----- | 620 A A ----- | 1709 lbs. | 44 psi | 11/32" | 28 lbs. | 6.5-8.5" | 7.5" | 9.6" | NA | 27.2" | 766 | US --- |
| 235/60R17 100T ----- | Pending ----- | | | 9/32" | 29 lbs. | 6.5-8.5" | 7" | 9.5" | NA | 28.1" | 740 | CA --- |
| 225/55R18 98H SL ----- | 620 A A ----- | 1653 lbs. | 44 psi | 11/32" | 27 lbs. | 6-8" | 7" | 9.2" | NA | 27.8" | 750 | US --- |
| 225/60R18 100H SL ----- | 620 A A ----- | 1764 lbs. | 44 psi | 11/32" | 29 lbs. | 6-8" | 6.5" | 9" | NA | 28.6" | 727 | US --- |
| 245/45R18 96V SL ----- | 620 A A ----- | 1565 lbs. | 44 psi | 11/32" | 28 lbs. | 7.5-9" | 8" | 9.6" | NA | 26.7" | 780 | US --- |
| 235/50R19 99V ----- | Pending ----- | | | 9/32" | 29 lbs. | 6.5-8.5" | 7.5" | 9.7" | NA | 28.3" | 735 | US --- |
| 245/45R20 99V SL ----- | 620 A A ----- | 1709 lbs. | 44 psi | | 31 lbs. | 0-0" | | | NA | NA | | CA --- |
| Size Service Description Load Range | UTQG | Max Load | Max. Inflation Press. | Tread Depth | Tire Weight | Rim Width Range | Meas. Rim Width | Sect. Width | Tread Width | Overall Diam. | Revs Per Mile | Country of Origin* |