



Harmony



Performance Category:
[All-Season](#)

ALL OTHER SIZES FOR THIS TIRE

Size Service Description Load Range	UTQG	Max Load	Max. Inflation Press.	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs Per Mile	Country of Origin*
175/70R13 82T SL	740 A B -----	1036 lbs.	44 psi	11/32"	16 lbs.	4.5-6"	5"	7"	NA	22.5"	923	GB ---
175/65R14 81S SL	740 A B -----	1019 lbs.	44 psi	11/32"	17 lbs.	5-6"	5"	7"	NA	22.9"	908	CA ---
175/70R14 84S SL	740 A B -----	1102 lbs.	44 psi	11/32"	18 lbs.	4.5-6"	5"	7"	NA	23.5"	883	CA ---
185/65R14 85S SL	740 A B -----	1124 lbs.	44 psi	11/32"	17 lbs.	5-6.5"	5.5"	7.5"	NA	23.4"	887	GB ---
185/70R14 87S SL	740 A B -----	1201 lbs.	44 psi	11/32"	19 lbs.	4.5-6"	5.5"	7.5"	NA	24.1"	865	IT --
195/65R14 88S SL	740 A B -----	1235 lbs.	44 psi	11/32"	20 lbs.	5.5-7"	6"	7.9"	NA	23.9"	872	CA ---
195/70R14 90S SL	740 A B -----	1312 lbs.	44 psi		21 lbs.	5-6.5"	6"	7.9"	NA	24.6"	846	IT --
205/70R14 93S SL	740 A B -----	1433 lbs.	44 psi	11/32"	22 lbs.	5-7"	6"	8.2"	NA	25.2"		CA ---
205/75R14 95S SL	740 A B -----	1532 lbs.	35 psi		24 lbs.	5-7"	5.5"	8"	NA	25.9"	803	CA ---
215/70R14 96S SL	740 A B -----	1554 lbs.	44 psi	11/32"	24 lbs.	5.5-7"	6.5"	8.6"	NA	25.7"		US ---
185/60R15 84T SL	740 A B -----	1102 lbs.	44 psi	11/32"	19 lbs.	5-6.5"	5.5"	7.5"	NA	23.6"	881	US ---
185/65R15 86T SL	740 A B -----	1168 lbs.	44 psi	11/32"	20 lbs.	5-6.5"	5.5"	7.5"	NA	24.5"		CA ---
195/60R15 87T SL	740 A B -----	1190 lbs.	44 psi	11/32"	21 lbs.	5.5-7"	6"	7.8"	NA	24"	866	CA ---
195/65R15 89T SL	740 A B -----	1279 lbs.	44 psi	11/32"	21 lbs.	5.5-7"	6"	7.8"	NA	24.8"	838	IT --
205/60R15 90S SL	740 A B -----	1301 lbs.	44 psi		22 lbs.	5.5-7.5"	6"	8.2"	NA	24.5"	847	CA ---
205/65R15 92T SL	740 A B -----	1400 lbs.	44 psi		22 lbs.	5.5-7.5"	6"	8.3"	NA	25.4"	821	US ---
205/70R15 95T SL	740 A B -----	1499 lbs.	44 psi	11/32"	25 lbs.	5-7"	6"	8.2"	NA	26.1"	796	CA ---
215/60R15 93T SL	740 A B -----	1411 lbs.	44 psi		23 lbs.	0-0"			NA	NA		US ---

Tire Specs for Michelin Harmony

215/65R15 95S SL -----	740 A B -----	1510 lbs.	44 psi	11/32"	24 lbs.	6-7.5"	6.5"	8.6"	NA	25.9"	803	CA ---
215/70R15 97T SL -----	740 A B -----	1602 lbs.	44 psi	11/32"	26 lbs.	5.5-7"	6.5"	8.6"	NA	26.6"	780	CA ---
205/55R16 89T SL -----	740 A B -----	1279 lbs.	44 psi	11/32"	22 lbs.	5.5-7.5"	6.5"	8.3"	NA	24.8"	839	US ---
205/60R16 91T SL -----	740 A B -----	1356 lbs.	44 psi	11/32"	24 lbs.	5.5-7.5"	6"	8.4"	NA	25.6"	813	US ---
215/60R16 94T SL -----	740 A B -----	1477 lbs.	44 psi		24 lbs.	0-0"			6.5"	NA		CA ---
215/65R16 98T SL -----	740 A B -----	1653 lbs.	44 psi	11/32"	25 lbs.	6-7"	6.5"	8.7"	NA	26.8"	775	US ---
225/60R16 97T SL -----	740 A B -----	1609 lbs.	44 psi	11/32"	26 lbs.	6-8"	6.5"	8.8"	NA	26.4"	787	US ---
225/55R17 95T SL -----	740 A B -----	1521 lbs.	44 psi		25 lbs.	0-0"			7.5"			US ---
225/60R17 98T SL -----	740 A B -----	1653 lbs.	44 psi		27 lbs.	0-0"			7.5"			US ---
Size Service Description Load Range	UTQG	Max Load	Max. Inflation Press.	Tread Depth	Tire Weight	Rim Width Range	Meas. Rim Width	Sect. Width	Tread Width	Overall Diam.	Revs Per Mile	Country of Origin*