



Available

Tire Size	Stock Number	Tread Depth (1/32")	Inflated Overall Dia. (in.)	Dimensions Overall Width (in.)	Approved Rim (measuring rim) Width (in.)	Maximum Load Press. (lbs) (psi)	Revs Per Mile
275/60R17 110V	202-380	11.2	29.96	10.83	7.5-(8.0)-9.5	2337@44	694
*235/55R18 104V	202-310	10.7	28.23	9.41	6.5-(7.5)-8.5	1984@50	736
*255/50R18 106V	202-250	11.0	28.00	10.30	7.0-(8.0)-9.0	2094@50	742
*255/55R18 109V	202-050	11.0	28.94	10.10	7.0-(8.0)-9.0	2271@50	718
*245/45R20 103V	202-190	10.8	28.62	9.45	7.5-(8.0)-9.0	1929@50	726
*255/40R20 101V	202-290	10.3	28.00	10.31	8.5-(9.0)-10.0	1819@50	742
*255/45R20 105V	202-110	11.0	29.13	9.88	8.0-(8.5)-9.5	2039@50	713
*255/50R20 109V	202-220	11.0	30.00	10.16	7.0-(8.0)-9.0	2271@50	692
*265/50R20 111V	202-060	11.1	30.47	10.91	7.5-(8.5)-9.5	2403@50	682
*275/55R20 117H	202-200	13.2	31.97	11.02	7.5-(8.5)-9.5	2833@50	650
*285/40R20 108V	202-150	10.7	28.94	11.38	9.5-(10.0)-11.0	2205@50	718
*285/50R20 116H	202-160	13.4	31.30	11.42	8.0-(9.0)-10.0	2756@50	664
*305/50R20 120H	202-020	13.6	32.05	12.44	8.5-(9.5)-11.0	3086@50	648
*265/35R22 102V	202-090	10.5	29.33	10.67	9.0-(9.5)-10.5	1874@50	708
*265/40R22 106V	202-350	10.5	30.35	10.55	9.0-(9.5)-10.5	2094@50	685
*275/40R22 108V	202-390	10.6	30.67	10.71	9.0-(9.5)-11.0	2205@50	677
*275/45R22 112H	202-370	13.2	31.73	10.67	8.5-(9.0)-10.5	2469@50	655
*285/35ZR22 106W	202-330	10.7	29.80	11.22	9.5-(10.0)-11.0	2094@50	697
*285/40R22 110V	202-300	11.1	31.14	11.38	9.5-(10.0)-11.0	2337@50	667
*285/45R22 114H	202-070	13.4	32.09	11.22	9.0-(9.5)-10.5	2601@50	647
*295/30R22 103V	202-120	10.8	29.01	11.50	10.0-(10.5)-11.0	1929@50	716
*305/40R22 114H	202-000	13.6	31.57	12.20	10.0-(11.0)-12.0	2601@50	658
*305/45R22 118H	202-010	13.6	32.60	11.83	9.5-(10.0)-11.5	2910@50	637
*305/40R23 115H	202-080	13.6	32.60	12.32	10.0-(11.0)-12.0	2679@50	637
*285/30R24 103V	202-320	10.7	30.87	11.02	9.5-(10.0)-10.5	1929@50	673
*285/35R24 108V	202-340	10.7	31.89	11.10	9.5-(10.0)-11.0	2205@50	651
*295/35R24 110H	202-100	13.5	32.09	11.65	10.0-(10.5)-11.5	2337@50	647
*305/35R24 112H	202-140	13.6	32.44	12.09	10.0-(11.0)-12.0	2469@50	640
*315/35R24 114H	202-130	13.7	32.72	12.24	10.5-(11.0)-12.5	2601@50	635
*305/30R26 109H	202-280	11.0	33.27	11.97	10.5-(11.0)-11.5	2271@50	624

* - Indicates Extra Load (XL) W - Indicates whitewall

All technical information subject to change without notice.

Passenger Tires used on Light Trucks & SUVs have reduced load capacities that differ from the maximum load listed. Diameter and width measurements are averages based on tires measured on specified measuring rim widths.