



NT555
SIZES AND SPECIFICATIONS

Tire Size	Stock Number	Tread Depth (1/32")	Inflated Overall Dia. (in.)	Dimensions Overall Width (in.)	Approved Rim (measuring rim) Width (in.)	Maximum Load Press. (lbs) (psi)	Revs Per Mile
*205/45ZR16 87W	182-110	9.8	23.15	8.31	6.5-(7.0)-7.5	1201@50	899
*205/40ZR17 84W	182-480	9.7	23.50	8.35	7.0-(7.5)-8.0	1102@50	884
*225/40ZR17 90W	182-340	10.1	24.06	9.02	7.5-(8.0)-9.0	1323@50	862
235/45ZR17 93W	182-200	10.2	25.28	9.33	7.5-(8.0)-9.0	1433@44	821
P245/45ZR17 89W	182-220	10.2	25.67	9.61	7.5-(8.0)-9.0	1279@35	811
255/40ZR17 94W	182-350	10.3	25.08	10.16	8.5-(9.0)-10.0	1477@44	829
P255/45ZR17 92W	182-240	10.2	25.95	10.08	8.0-(8.5)-9.5	1389@35	800
255/50ZR17 101W	182-830	10.3	27.09	10.43	7.0-(8.0)-9.0	1819@44	767
P275/40ZR17 98W	182-370	10.6	25.59	11.02	9.0-(9.5)-11.0	1653@44	813
P285/40ZR17 95W	182-380	10.1	25.95	11.38	9.5-(10.0)-11.0	1521@35	800
315/35ZR17 102W	182-870	10.7	25.62	12.56	10.5-(11.0)-12.5	1874@44	811
*215/35ZR18 84W	182-490	9.8	23.94	8.31	7.0-(7.5)-8.5	1102@50	868
*225/35ZR18 87W	182-500	10.0	24.17	8.98	7.5-(8.0)-9.0	1201@50	859
*225/40ZR18 92W	152-430	10.1	25.04	9.02	7.5-(8.0)-9.0	1389@50	829
*225/45ZR18 95W	182-410	10.0	25.94	8.82	7.0-(7.5)-8.5	1521@50	800
235/40ZR18 91W	182-430	10.2	25.28	9.45	8.0-(8.5)-9.5	1356@44	821
*235/50ZR18 101W	182-860	10.1	27.24	9.45	6.5-(7.5)-8.5	1819@50	762
245/40ZR18 93W	182-440	10.2	25.67	9.72	8.0-(8.5)-9.5	1433@44	811
*245/45ZR18 100W	182-710	10.0	26.57	9.65	7.5-(8.0)-9.0	1764@50	782
255/35ZR18 90W	182-520	10.3	25.08	10.08	8.5-(9.0)-10.0	1323@44	829
*255/45ZR18 103W	181-960	10.3	26.97	10.16	8.0-(8.5)-9.5	1929@50	770
265/35ZR18 93W	182-530	10.5	25.28	10.47	9.0-(9.5)-10.5	1433@44	821
265/50ZR18 103W	182-880	10.5	28.43	10.83	7.5-(8.5)-9.5	1929@44	731
275/35ZR18 95W	182-250	10.6	25.59	10.71	9.0-(9.5)-11.0	1521@44	812
*275/40ZR18 103W	181-970	10.1	26.61	10.91	9.0-(9.5)-11.0	1929@50	781
285/35ZR18 97W	182-550	10.5	25.95	11.30	9.5-(10.0)-11.0	1609@44	800
285/40ZR18 101W	182-800	10.7	26.97	11.42	9.5-(10.0)-11.0	1819@44	770
*295/45ZR18 112W	182-290	10.8	28.31	11.54	9.5-(10.0)-11.0	2469@50	734
*225/35ZR19 88W	182-600	10	25.16	8.94	7.5-(8.0)-9.0	1235@50	826
*235/35ZR19 91W	182-610	10.1	25.51	9.37	8.0-(8.5)-9.5	1356@50	814
*245/35ZR19 93W	182-620	10.2	25.87	9.65	8.0-(8.5)-9.5	1433@50	801
*265/30ZR19 93W	182-670	10.5	25.39	10.59	9.0-(9.5)-10.0	1433@50	818
*275/30ZR19 96W	182-680	10.6	25.63	10.87	9.0-(9.5)-10.0	1565@50	811
*275/35ZR19 100W	182-810	10.6	26.57	10.94	9.0-(9.5)-11.0	1764@50	782
*225/35ZR20 90W	181-980	10.0	26.22	9.05	7.5-(8.0)-9.0	1323@50	791
*235/35ZR20 92W	182-450	10.1	26.42	9.57	8.0-(8.5)-9.5	1389@50	786
*245/30ZR20 90W	182-780	10.2	25.83	9.76	8.0-(8.5)-9.0	1323@50	804
*245/35ZR20 95W	182-650	10.2	26.69	9.65	8.0-(8.5)-9.5	1521@50	778
*245/40ZR20 99W	182-840	10.2	27.72	9.76	8.0-(8.5)-9.5	1709@50	749
*255/35ZR20 97W	182-660	10.3	27.05	10.24	8.5-(9.0)-10.0	1609@50	768
255/45ZR20 101W	182-890	10.3	29.02	10.08	8.0-(8.5)-9.5	1819@44	716
*265/35ZR20 99W	182-820	10.5	27.32	10.67	9.0-(9.5)-10.5	1709@50	760
*275/30ZR20 97W	182-700	10.6	26.61	10.71	9.0-(9.5)-10.0	1609@50	781
*275/35ZR20 102W	182-640	10.6	27.60	10.91	9.0-(9.5)-11.0	1874@50	753
*285/30ZR20 99W	182-790	10.7	26.93	11.02	9.5-(10.0)-10.5	1709@50	771
*255/30ZR22 95W	182-850	10.0	28.11	10.08	8.5-(9.0)-9.5	1521@50	739
*265/40ZR22 106W	182-400	10.5	30.39	10.55	9.0-(9.5)-10.5	2094@50	683
*285/35ZR22 106W	182-590	10.7	29.88	11.22	9.5-(10.0)-11.0	2094@50	695
*295/25ZR22 97W	182-770	10.1	27.91	11.42	10.0-(10.5)-11.0	1609@50	744
*295/30ZR23 104W	182-360	10.1	30.00	11.65	10.0-(10.5)-11.0	1984@50	692

* - Indicates Extra Load (XL)

Nitto Tire: Tire Sizes and Specs - NT555

All technical information subject to change without notice.

Passenger Tires used on Light Trucks & SUVs have reduced load capacities that differ from the maximum load listed. Diameter and width measurements are averages based on tires measured on specified measuring rim widths.