



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (1/32")	Overall Diameter (inch)	Overall Width (inch)	Static Loaded Radius (inch)	Max Load (lbs)	Max. Pressure (psi)	UTQG	Revs Per Mile
245/70R16 107V	242660	6.5-7.0-8.0	34	11	29.6	9.7	13.3	2149	44	420 A A	702
275/60R16 109V	242180	7.5-8.0-9.5	40	11	29	11	13	2271	44	420 A A	720
255/55R18 109V RD	242160	7.0-8.0-9.0	34	11	29	10.4	13.3	2271	50	420 A A	718
255/40R20 101V RD	242700	8.5-9.0-10.0	29.8	10	28	10.1	13.1	1819	50	420 A A	743
255/50R20 109V RD	242490	7.0-8.0-9.0	30.9	11	29.9	10.2	13.9	2271	50	420 A A	694
265/50R20 111V RD	242330	7.5-8.5-9.5	39	11	30.4	11	14.1	2403	50	420 A A	683
275/40R20 106WRD	242740	9.0-9.5-11.0	34	11	28.6	10.8	13.3	2094	50	420 A A	727
275/45R20 110V RD	242790	8.5-9.0-10.5	33.5	11	29.8	10.6	13.8	2337	50	420 A A	698
275/55R20 117V RD	242800	7.5-8.5-9.5	41.5	11	31.9	11	14.6	2833	50	420 A A	652
285/50R20 116V RD	242710	8.0-9.0-10.0	41.9	11	31.1	11.6	14.3	2756	50	420 A A	669
295/45R20 114V RD	242320	9.5-10.0-11.0	40	11	30.5	11.7	14.1	2601	50	420 A A	683
305/50R20 120V RD	242350	8.5-9.5-11.0	44.7	11	32.1	12.4	14.6	3086	50	420 A A	651
325/50R20 120V	242340	9.0-10.0-11.5	48.9	12	32.8	13.2	12.7	3086	44	420 A A	636
265/35R22 102WRD	242760	9.0-9.5-10.5	34.2	10	29.3	10.4	13.9	1874	50	420 A A	708
265/40R22 106V RD	242460	9.0-9.5-10.5	45	10	30.4	10.7	14.3	2094	50	420 A A	684
285/35R22 106WRD	242750	9.5-10.0-11.0	37	11	29.8	11.3	14	2094	50	420 A A	697
285/45R22 114V RD	242690	9.0-9.5-10.5	41.9	11	32.2	11.2	15	2601	50	420 A A	645
305/40R22 114V RD	242390	10.0-10.5-12.0	45	11	31.6	12.3	14.8	2601	50	420 A A	657
305/45R22 118V RD	242370	9.5-10.0-11.5	48	11	32.8	12	15.2	2910	50	420 A A	636
315/30R22 107Y RD	242830	10.5-11.0-11.5	37.5	11	29.5	12.2	13.9	2149	50	280 A A	704
325/50R22 120V	242680	9.0-10.0-11.5	60.6	11	34.7	13	15.9	3086	44	420 A A	599
285/40R24 112VRD	242720	9.5-10.0-11.0	46.3	11	32.9	11.3	15.5	2469	50	420 A A	631
305/35R24 112VRD	242820	10.0-11.0-12.0	41.9	11	32.5	12.1	15.3	2469	50	420 A A	640

305/30R26 109V RD	242850	10.5-11.0-11.5	44.5	11	33.1	12.1	15.8	2271	50	A	628
325/45R24 120V	242730	10.0-11.0-12.0	54	11	35.4	12.6	16.4	3086	44	420 A A	588
305/30R26 109V RD	242850	10.5-11.0-11.5	44.5	11	33.1	12.1	15.8	2271	50	420 A A	628

Bold designates measuring rim width

RD = Reinforced

XL = Extra load

LL = [Light Load](#)

For Passenger Tires: * Whitewall (All other sizes blackwall)

For Light Truck Tires: * White letter styling

Light Truck Construction Elements: Tread: 3P = 3-Ply Polyester Casing, 2P = 2-Ply Polyester Casing, 2S = 2 Steel Belts, 2N = 2 Nylon Cap Plies, 1N = 1 Nylon Cap Ply **Sidewall:** 3P = 3 Ply Polyester

All Toyo brand tires are subject to continuous development. Toyo Tire U.S.A. Corp. reserves the right to change construction, materials or specifications without notice or obligation. Contact your Toyo Tires dealer or Toyo Tires for current information.