



Tire Size	Product Code	Approved Rim Width Range (inch)	Tire Weight (lbs.)	Tread Depth (1/32")	Overall Diameter (inch)	Overall Width (inch)	Static Loaded Radius (inch)	Max Load: Single (lbs)	Max Load: Dual (lbs)	Max. Pressure Single (psi)	Max. Pressure: Dual (psi)
31X10.50R15LT 109Q C/6	360490	7.0- 8.5 -9.0	55.1	19	31.1	10.7	14.5	2270		50	
33X10.50R15LT 114P C/6	360470	7.0- 8.5 -9.0	57.3	19	32.8	10.9	15.2	2600		50	
33x12.50R15LT 108P C/6	360100	8.0- 10.0 -11.0	69.4	21	33	12.8	15.4	2205		35	
33X13.50R15LT 109Q C/6	360290	8.5- 11.0	75	21	33.1	13.9	15.4	2270		35	
35X13.50R15LT 114Q C/6	361000	8.50- 11.0	79.4	21	34.8	14.4	15.2	2600		35	
37X14.50R15LT 120Q C/6	360260	10.0- 12.0	93.7	21	36.7	15.6	17	3080		35	
LT235/85R16 120/116P E/10	360440	6.0- 6.5 -7.5	51.8	18	32	9.4	14.9	3042		80	
LT245/75R16 120/116P E/10	360450	6.5- 7.0 -8.0	51.8	18	30.7	9.9	14.3	3042		80	
LT255/85R16 123/120P E/10 (33X10.00R16)	360460	6.5- 7.0 -8.0	59.5	19	33.5	10.2	15.6	3415		80	
LT265/75R16 123P E/10	360320	7.0- 7.5 -8.0	58.4	19	31.8	10.8	14.8	3415		80	
LT285/70R16 114P C/6	360170	7.5- 8.5 -9.5	60.6	19	32	11.1	14.9	2600		50	
LT285/75R16 126P E/10 (33X11.50R16)	360280	7.5- 8.0 -9.0	68.3	19	33	11.6	15.4	3740		80	
LT305/70R16 124P E/10 (33.0X12.00R16)	360110	8.0- 9.0 -9.5	71.7	20	33	12.2	15.4	3525		65	
LT315/75R16 127Q E/10 (35X12.50R16)	360230	8.0- 8.5 -10.0	76.1	21	34.9	12.9	16.2	3860		65	
LT385/70R16 130Q D/8 (38X15.00R16)	360480	10.0- 11.0 -12.0	97	21	37.7	15.6	17.5	4190		50	
38X14.50R16LT 129Q D/8	360250	10.0- 12.0	99.2	21	37.7	15.6	17.5	4080		50	
LT265/70R17 121P E/10	360130	7.0- 8.0 -8.5	62.8	19	32	10.8	14.9	3195		80	
LT285/75R17 121P E/10 (34X11.50R17)	360430	7.5- 8.0 -9.5	70.6	19	34.1	11.6	15.8	3195		80	
LT295/70R17 128P E/10 (33X11.50R17)	360360	8.0- 8.5 -9.5	72.8	19	33.5	12	15.6	3970		80	
35X12.50R17LT 125Q E/10	360310	8.5- 10.0 -11.0	82.7	21	34.8	13.2	16.2	3640		65	
37X13.50R17LT 131Q E/10	360270	8.5- 11.0	92.6	21	37	14.6	17.2	4300		65	
LT275/70R18 125P E/10 (33X11.00R18)	360120	7.0- 8.0 -8.5	66.1	19	33.6	11	15.6	3640		80	
LT285/75R18 129P E/10 (35X11.5R18)	360420	7.5- 8.0 -9.5	70.6	19	35.1	11.6	16.3	4080		80	
LT315/70R18 127/124Q E/10 (36X13.00R18)	360560	8.0- 9.5 -11.0	81.6	21	35.7	13	16.6	3860	3525	65	65
33X12.50R18LT 118Q E/10	360340	8.5- 10.0 -11.0	75	21	33	12.7	15.3	2910		65	
35X12.50R18LT 123Q E/10	360090	8.5- 10.0 -11.0	80.9	21	35	13.2	15.6	3415		65	
37X13.50R18LT 124Q D/8	360300	8.5- 11.0	92.6	21	37	14.2	17.2	3525		50	
38x13.50R18LT 126Q D/8	360380	8.50- 11.0	97	21	37.7	14.3	17.5	3750		50	
38X15.50R18LT 128Q D/8	360180	11.0- 12.0 -13.0	105.8	21	37.7	15.9	17.5	3970		50	
LT275/65R20 126P E/10 (34X11.00R20)	360410	7.5- 8.0 -9.5	70.6	19	34.5	11	16	3750		80	
LT315/60R20 125/122Q E/10 (35X12.50R20)	360510	8.5- 9.5 -11.0	78.3	21	35	12.6	16.3	3640	3305	65	65
33X12.50R20LT 114Q E/10	360330	8.5- 10.0 -11.0	71.7	21	33	12.6	15.3	2600		65	
35X12.50R20LT 121Q E/10	360240	8.5- 10.0 -11.0	80.5	21	35	13	16.3	3195		65	
37X13.50R20LT 127Q E/10	360220	8.5- 11.0	93.7	21	37	14	17.2	3860		65	
38X13.50R20LT 124Q D/8	360390	8.50- 11.0	100.3	21	37.7	14.3	17.5	3525		50	
38X15.50R20LT 125Q D/8	360190	11.0- 12.0 -13.0	101.4	21	37.7	15.9	17.5	3640		50	
40X15.50R20LT 130Q D/8	360370	11.0- 12.0 -13.0	112.4	21	39.7	15.9	18.4	4190		50	
33X12.50R22LT 109Q E/10	360520	8.5- 10.0 -11.0	70.6	19	33	12.4	15.3	2270		65	
35X12.50R22LT 117Q E/10	360540	8.5- 10.0 -11.0	80.5	21	35	12.8	16.3	2835		65	
37X13.50R22LT 123Q E/10	360210	8.5- 11.0	90.4	21	37	14	17.2	3420		65	
40X15.50R22LT 127Q D/8	360200	11.0- 12.0 -13.0	110.2	21	39.7	15.9	18.5	3860		50	
37X13.50R24LT 120Q E/10	360350	8.5- 11.0	89.3	21	37	13.6	17.2	3085		65	

Bold designates measuring rim width

RD = Reinforced

XL = Extra load

For Passenger Tires: * Whitewall (All other sizes blackwall)

For Light Truck Tires: * White letter styling