



TIRES

DEALER LOCATOR

CUSTOMER SERVICE

MOTORSPORTS

CORPORATE

NEWSROOM

 BACK

## AVID T4

Tire Size	Part#	Load ID	UTQG Rating	Unit Weight (lbs)	Rim Width (inches)		Inflated Dimensions		Tread Width	Tread Depth 32/in	Loaded Dimensions		Max Load at Cold Inflation Pressure (lbs. @psi) Single	Type
					Meas.	Appr.	Overall Width (inches)	Overall Diameter (inches)			Static Radius (inches)	Rev/ Mile		
P175/65R14 81T	30468	SL	420/A/B	15.17	5.0	5.0 - 6.0	6.9	23.0	5.1	10	10.4	904	1019@35	BW
P185/65R14 85T	30469	SL	420/A/B	16.36	5.5	5.0 - 6.5	7.4	23.5	5.4	10	10.5	885	1124@35	BW
P185/70R14 87T	30482	SL	420/A/B	16.93	5.5	4.5 - 6.0	7.5	24.3	5.7	11	11	856	1201@35	BW
P195/70R14 90T	30483	SL	420/A/B	18.50	6.0	5.0 - 6.5	8.0	24.8	6.0	11	11.2	836	1312@35	BW
P205/70R14 93T	30484	SL	420/A/B	19.33	6.0	5.0 - 7.0	8.3	25.4	6.5	11	11.4	819	1433@35	BW
P185/65R15 86T	30471	SL	420/A/B	17.38	5.5	5.0 - 6.5	7.4	24.5	5.4	10	11.0	849	1168@35	BW
P195/55R15 84T	30488	SL	420/A/B	18.72	6.0	5.5 - 7.0	7.9	23.4	6.5	11	10.7	887	1102@35	BW
P205/50R15 84T	30489	SL	420/A/B	19.95	6.5	5.5 - 7.5	8.3	23.1	6.7	11	10.5	897	1113@35	BW
P205/60R15 90T	30464	SL	420/A/B	19.37	6.0	5.5 - 7.5	8.1	24.7	6.1	11	11.1	840	1301@35	BW
P205/65R15 92T	30473	SL	420/A/B	20.05	6.0	5.5 - 7.5	8.3	25.4	6.2	11	11.2	818	1400@35	BW
P205/70R15 95T	30486	SL	420/A/B	21.21	6.0	5.0 - 7.0	8.3	26.3	6.2	11	11.7	790	1499@35	BW
P215/60R15 93T	30465	SL	420/A/B	21.64	6.5	6.0 - 7.5	8.7	25.2	6.3	11	11.3	824	1411@35	BW
P215/65R15 95T	30474	SL	420/A/B	22.69	6.5	6.0 - 7.5	8.8	26.0	6.5	11	12.0	799	1510@35	BW
P215/70R15 97T	30487	SL	420/A/B	23.86	6.5	5.5 - 7.0	8.9	26.9	6.6	11	12.0	773	1620@35	BW
P225/50R15 90T	30490	SL	420/A/B	22.10	7.0	6.0 - 8.0	9.1	23.9	7.3	11	10.7	869	1301@35	BW
P205/55R16 89T	30477	SL	420/A/B	22.36	6.5	5.5 - 7.5	8.3	24.8	7.0	10	12.0	836	1279@35	BW
P205/60R16 91T	30491	SL	420/A/B	22.84	6.0	5.5 - 7.5	8.2	25.7	6.4	11	11.7	809	1356@35	BW
P215/60R16 94T	30492	SL	420/A/B	22.50	6.5	6.0 - 7.5	8.8	26.1	6.7	11	11.7	795	1477@35	BW
P225/60R16 97T	30467	SL	420/A/B	24.34	6.5	6.0 - 8.0	8.9	26.7	7.2	10	12.2	778	1609@35	BW
P235/55R16 96T	30478	SL	420/A/B	24.69	7.5	6.5 - 8.5	9.6	26.2	7.9	10	12.0	793	1565@35	BW
P225/55R17 95T	30494	SL	420/A/B	26.52	7.0	6.0 - 8.0	9.1	26.7	7.4	11	12.0	777	1521@35	BW

