

 **BACK**

AVID Touring-S

Tire Size	Part#	Load ID	UTQG Rating	Unit Weight (lbs)	Rim Width (inches)		Inflated Dimensions		Tread Width	Tread Depth 32/in	Loaded Dimensions		Max Load at Cold Inflation Pressure (lbs. @psi) Single	Type
					Meas.	Appr.	Overall Width (inches)	Overall Diameter (inches)			Static Radius (inches)	Rev/ Mile		
P175/65R14 81S	31801	SL	620/A/B	15.84	5.0	5.0-6.0	7.0	23.1	5.3	10	10.5	900	1019@51	BW
P185/65R14 85S	31802	SL	620/A/B	17.82	5.5	5.0-6.5	7.4	23.5	5.6	10	10.7	885	1124@51	BW
P185/70R14 87S	31803	SL	620/A/B	18.04	5.5	4.5-6.0	7.5	24.3	5.7	10	11	856	1201@51	BW
P195/70R14 90S	31804	SL	620/A/B	18.70	6.0	5.0-6.5	8.0	24.8	6.0	10	11.2	837	1312@51	BW
P185/60R15 84T	31805	SL	620/A/B	17.82	5.5	5.0-6.5	7.4	23.7	5.9	10	10.9	875	1102@51	BW
P185/65R15 86S	31806	SL	620/A/B	18.26	5.5	5.0-6.5	7.4	24.4	5.6	10	11.2	850	1168@51	BW
P195/60R15 87T	31807	SL	620/A/B	19.14	6.0	5.5-7.0	7.8	24.3	6.2	10	11.1	856	1190@51	BW
P195/65R15 89S	31808	SL	620/A/B	19.63	6.0	5.5-7.0	8.0	25.0	5.9	10	11.4	831	1279@51	BW
P205/65R15 92S	31809	SL	620/A/B	20.68	6.0	5.5-7.5	8.3	25.4	6.2	10	11.6	818	1400@51	BW
P205/70R15 95S	31810	SL	620/A/B	22.00	6.0	5.0-7.0	8.2	26.4	6.5	10	11.9	787	1499@51	BW
P215/60R15 93T	31811	SL	620/A/B	21.12	6.5	6.0-7.5	8.7	25.1	6.9	10	11.4	827	1411@51	BW
P215/65R15 95S	31812	SL	620/A/B	21.78	6.5	6.0-7.5	8.9	25.9	6.7	10	11.8	801	1510@51	BW
215/70R15 98S	31813	SL	620/A/B	23.76	6.5	5.5-7.0	8.9	26.9	6.9	10	12.1	774	1653@51	BW
P205/55R16 89T	31814	SL	620/A/B	21.34	6.5	5.5-7.5	8.5	24.9	7.0	10	11.5	835	1279@51	BW
P205/60R16 91T	31815	SL	620/A/B	21.34	6.0	5.5-7.5	8.2	25.6	6.5	10	11.8	810	1356@51	BW
P215/60R16 94T	31816	SL	620/A/B	22.22	6.5	6.0-7.5	8.8	26.1	6.9	10	12.0	794	1477@51	BW
215/65R16 98T	31817	SL	620/A/B	24.20	6.5	6.0-7.5	8.7	27.0	6.9	10	12.3	770	1653@51	BW
P225/60R16 97S	31818	SL	620/A/B	24.64	6.5	6.0-8.0	9.0	26.6	7.2	10	12.1	780	1609@51	BW
P225/60R17 98T	31819	SL	620/A/B	27.72	6.5	6.0-8.0	8.9	27.7	7.2	10	12.7	749	1653@51	BW

