

 **BACK**

## GEOLANDAR H/T-S

Tire Size	Part#	Load ID	UTQG Rating	Unit Weight (lbs)	Rim Width (inches)		Inflated Dimensions		Tread Width	Tread Depth 32/in	Loaded Dimensions		Max Load at Cold Inflation Pressure (lbs. @psi) Single	Type
					Meas.	Appr.	Overall Width (inches)	Overall Diameter (inches)			Static Radius (inches)	Rev/ Mile		
P235/75R15 108S	05114	XL	500/A/B	32.90	6.5	6.0 - 8.0	9.3	28.9	7.2	11	12.9	719	2183@41	OWL
P265/70R15 110S	05121	SL	500/A/B	38.50	8.0	7.0 - 9.0	10.8	29.7	8.1	12	13.2	700	2337@35	OWL
P265/75R15 112S	05123	SL	500/A/B	40.50	7.5	7.0 - 9.0	10.6	30.7	8.1	12	13.6	676	2469@35	OWL
P215/70R16 99S	05110	SL	500/A/B	26.50	6.5	5.5 - 7.0	8.7	28.0	6.5	11	12.7	742	1709@35	OWL
P225/70R16 101S	05111	SL	500/A/B	31.55	6.5	6.0 - 7.5	8.9	28.5	6.9	11	12.9	730	1819@35	OWL
P225/75R16 106S	05112	XL	500/A/B	32.50	6.0	6.0 - 7.5	8.7	29.3	6.9	11	13.2	710	2094@50	OWL
P235/70R16 104S	05113	SL	500/A/B	33.73	7.0	6.0 - 8.0	9.5	29.1	7.2	11	13.1	713	1984@35	OWL
P235/75R16 109S	05115	XL	500/A/B	34.50	6.5	6.0 - 8.0	9.2	29.9	7.2	11	13.4	694	2271@41	OWL
P245/70R16 106S	05116	SL	500/A/B	35.40	7.0	6.5 - 8.0	9.8	29.6	7.5	11	13.3	702	2094@44	OWL
P245/75R16 109S	05117	SL	500/A/B	36.90	7.0	6.5 - 8.0	10.0	30.5	7.5	11	13.6	682	2271@35	OWL
P255/65R16 106S	05118	SL	500/A/B	35.10	7.5	7.0 - 9.0	10.3	29.0	7.8	11	13.1	716	2094@51	OWL
P255/70R16 112S	05119	XL	500/A/B	36.80	7.5	6.5 - 8.5	10.2	30.3	7.8	12	13.6	686	2469@41	OWL
P265/70R16 111S	05122	SL	500/A/B	40.11	8.0	7.0 - 9.0	10.9	30.7	8.1	12	13.7	677	2403@35	OWL
P265/75R16 114T	05134	SL	500/A/B	30.86	7.5	7.0 - 9.0	10.7	31.7	8.1	11	14.1	655	2601@44	OWL
P275/70R16 114S	05124	SL	500/A/B	41.50	8.0	7.0 - 9.0	11.0	31.3	8.4	12	13.9	664	2601@35	OWL
235/65R17 108H	05201	RF	460/A/A	32.80	7.0	6.5 - 8.5	9.4	29.1	7.2	11	13.2	714	2205@50	RBL
P235/70R17 108S	05127	XL	500/A/B	38.81	7.0	6.0 - 8.0	9.5	30.2	7.2	11	13.6	689	2205@50	RBL
P245/65R17 105S	05128	SL	500/A/B	33.62	7.0	7.0 - 8.5	9.8	29.4	7.5	11	13.4	705	2039@51	RBL
P245/70R17 108S	05129	SL	500/A/B	40.47	7.0	6.5 - 8.0	9.8	30.6	7.5	11	13.8	679	2205@51	RBL
P255/65R17 108S	05130	SL	500/A/B	40.70	7.5	7.0 - 9.0	10.3	30.0	7.8	11	13.6	691	2205@51	RBL
P265/65R17 110S	05132	SL	500/A/B	42.37	8.0	7.5 - 9.5	10.7	30.4	8.1	11	13.7	682	2337@51	RBL
P265/70R17 113S	05101	SL	500/A/B	42.50	8.0	7.0 - 9.0	10.7	31.8	8.1	12	14.3	653	2535@35	OWL
275/55R17 109H	05204	SL	460/A/A	41.10	8.5	7.5 - 9.5	11.1	28.9	9.4	12	13.1	720	2271@44	RBL
P275/60R17 110H	05102	SL	460/A/A	37.60	8.0	7.5 - 9.5	11.1	29.9	8.7	12	13.5	694	2337@35	RBL
255/55R18 109H	05202	RF	460/A/A	37.71	8.0	7.0 - 9.0	10.4	29.1	8.7	11	13.3	713	2271@50	RBL
P255/70R18 112S	05131	SL	500/A/B	41.08	7.5	6.5 - 8.5	10.3	32.2	7.8	12	14.5	645	2469@51	RBL
265/60R18 110H	05203	SL	460/A/A	41.50	8.0	7.5 - 9.5	10.8	30.5	8.4	11	13.9	681	2337@44	RBL
P275/65R18 114H	05133	SL	500/A/B	41.59	7.5	7.5 - 9.5	10.3	32.2	8.4	12	14.5	645	2601@51	BW
285/60R18 120H	05205	RF	460/A/A	42.07	8.5	8.0 - 10.0	11.5	31.4	9.1	11	14.2	661	3086@50	RBL
P275/45R20 106H	05206	SL	460/A/A	39.61	9.0	8.5 - 10.0	10.8	29.7	10.0	11	13.8	699	2094@44	RBL
P275/55R20 111H	05211	SL	460/A/A	42.79	8.5	7.5 - 9.5	11.1	32.0	9.4	11	14.7	650	2403@51	RBL
285/50R20 112V	05212	SL	460/A/A	42.80	9.0	8.0 - 10.0	11.7	31.3	9.7	12	14.4	664	2469@44	BW
305/50R20 120H	05208	RF	460/A/A	46.72	9.5	8.5 - 11.0	12.5	32.1	10.3	12	14.7	647	3086@50	RBL
305/40R22 114H	05209	RF	460/A/A	43.96	11.0	10.0 - 12.0	12.0	31.6	11.1	12	14.8	657	2601@50	RBL
305/45R22 118H	05210	RF	460/A/A	45.19	10.0	9.5 - 11.5	11.8	32.9	10.7	11	15.3	631	2910@50	RBL
LT215/75R15 100/97Q	05105	C		31.68	6.0	5.5 - 7.0	8.5	27.8	6.5	13	12.9	748	1765@50	OWL

(C)	05103	C		31.98	6.5	6.0 - 7.0	8.5	27.8	6.3	13	12.5	740	1785@50	OWL
LT235/75R15 104/101Q (C)	05107	C		34.59	6.5	6.0 - 7.0	9.4	29.1	7.2	14	13.5	714	1985@50	OWL
LT215/85R16 115/112Q (E)	05351	E		41.78	6.0	5.5 - 7.0	8.5	30.4	6.3	13	14.2	682	2680@80	ORB
LT225/75R16 110/107Q (D)	05106	D		38.92	6.0	6.0 - 7.0	8.8	29.4	6.9	13	13.7	705	2335@65	OWL
LT235/85R16 120/116Q (E)	05352	E		48.63	6.5	6.0 - 7.0	9.5	31.8	7.2	14	14.7	654	3042@80	ORB
LT245/75R16 120/116Q (E)	05353	E		46.48	7.0	6.5 - 7.5	9.8	30.6	7.5	14	14.2	680	3042@80	ORB
LT265/75R16 123/120Q (E)	05354	E		50.86	7.5	7.0 - 8.0	10.4	31.7	8.1	14	14.6	656	3415@80	BW
LT265/75R16 119/116Q (D)	05108	D		45.67	7.5	7.0 - 8.0	10.6	31.8	8.1	14	14.7	653	3000@65	OWL
LT285/75R16 122/119Q (D)	05109	D		50.92	8.0	7.5 - 9.0	11.5	33.0	8.7	15	15.2	630	3305@65	OWL
LT235/80R17 120/117Q (E)	05356	E		46.65	6.0	6.0 - 7.5	9.1	31.7	7.2	14	15.0	653	3085@80	RBL
LT245/70R17 119/116Q (E)	05358	E		42.11	7.0	6.5 - 8.0	9.4	30.6	7.5	14	14.5	677	3000@80	RBL
LT245/70R17 114/110Q (D)	05125	D		38.14	7.0	6.5 - 8.0	9.8	30.9	7.5	14	14.2	673	2600@65	RBL
LT265/70R17 E642 (E)	05357	E		50.06	8.0	7.0 - 8.5	10.4	31.6	8.1	14	15.1	653	3195@80	RBL
LT315/70R17 121/118R (D)	05126	D		58.64	9.5	8.5 - 10.0	12.4	34.4	9.5	16	16.2	604	3195@50	BW
30X9.50R15 LT 104Q (C)	05103	C		36.49	7.5	6.5 - 8.5	9.8	29.6	7.4	15	13.7	701	1985@50	OWL
31X10.50R15 LT 109Q (C)	05104	C		41.95	8.5	7.0 - 9.0	10.7	30.6	8.2	15	14.1	680	2270@50	OWL

