



TIRES

DEALER LOCATOR

CUSTOMER SERVICE

MOTORSPORTS

CORPORATE

NEWSROOM

 BACK

GEOLANDAR AT-S

Tire Size	Part#	Load ID	UTQG Rating	Unit Weight (lbs)	Rim Width (inches)		Inflated Dimensions		Tread Width	Tread Depth 32/in	Loaded Dimensions		Max Load at Cold Inflation Pressure (lbs. @psi) Single	Type
					Meas.	Appr.	Overall Width (inches)	Overall Diameter (inches)			Static Radius (inches)	Rev/ Mile		
205/70R15 96S	01229	SL	500/A/B	24.69	6.00	5.0 - 7.0	8.3	26.5	6.4	12	12.0	783	1565@51	RBL
215/70R15 98S	01261	SL	500/A/B	26.24	6.5	5.5 - 7.0	8.8	26.9	6.7	12	12.1	774	1653@51	RBL
P225/70R15 100S	01258	SL	500/A/B	29.10	6.5	6.0 - 7.5	9.1	27.6	7.0	12	12.4	753	1753@51	OWL
P235/70R15 102S	01245	SL	500/A/B	31.09	7.0	6.0 - 8.0	9.6	28.0	7.3	13	12.6	743	1896@51	OWL
P235/75R15 108S	01235	XL	500/A/B	34.17	6.5	6.0 - 8.0	9.3	28.9	7.3	13	12.9	720	2183@50	OWL
265/70R15 112S	01228	SL	500/A/B	38.14	8.0	7.0 - 9.0	10.9	29.7	8.3	13	13.2	700	2469@51	RBL
215/60R16 95H	01259	SL	500/A/A	25.13	6.5	6.0 - 7.5	8.7	26.1	6.7	12	11.9	796	1521@51	RBL
215/65R16 98H	01260	SL	500/A/A	26.24	6.5	6.0 - 7.5	8.7	27.0	6.7	12	12.3	768	1653@51	RBL
215/70R16 100S	01224	SL	500/A/B	28.00	6.5	5.5 - 7.0	8.6	28.0	6.7	12	12.7	742	1764@51	RBL
225/70R16 102H	01262	SL	500/A/B	30.40	6.5	6.0 - 7.5	9.1	28.3	7.0	12	12.8	734	1874@51	RBL
235/60R16 100H	01253	SL	500/A/A	28.22	7.0	6.5 - 8.5	9.4	27.0	7.3	12	12.3	769	1764@51	RBL
P235/70R16 107S	01239	XL	500/A/B	33.73	7.0	6.0 - 8.0	9.5	29.2	7.3	13	13.2	711	2149@50	OWL
P245/70R16 106S	01236	SL	500/A/B	34.83	7.0	6.5 - 8.0	9.8	29.7	7.6	13	13.3	700	2094@51	OWL
255/65R16 109H	01241	SL	500/A/A	35.24	7.5	7.0 - 9.0	10.4	29.1	8.0	13	13.1	713	2271@51	RBL
P255/70R16 109S	01238	SL	500/A/B	37.04	7.5	6.5 - 8.5	10.2	30.3	8.0	13	13.6	685	2271@51	OWL
P265/70R16 111S	01233	SL	500/A/B	39.24	8.0	7.0 - 9.0	10.9	30.7	8.3	13	13.7	676	2403@51	OWL
275/70R16 114S	01240	SL	500/A/B	42.67	8.0	7.0 - 9.0	10.9	31.4	8.6	13	14.0	662	2601@51	RBL
215/60R17 96H	01299		500/A/A	26.80	6.5	6.0-7.5	8.7	27.1	6.7	12	12.4	767	1565@51	BW
225/60R17 99H	01263	SL	500/A/A	29.72	6.5	6.0 - 8.0	9.1	27.6	7.0	12	12.6	751	1709@51	RBL
225/65R17 102H	01266	SL	500/A/A	31.09	6.5	6.0 - 7.5	9.1	28.5	7.0	12	13.0	728	1874@51	RBL
225/70R17 108T	01267	RF	500/A/B	33.20	6.5	6.0 - 7.5	9.1	29.6	7.0	13	13.4	701	2205@50	RBL
235/65R17 108H	01247	RF	500/A/A	33.73	7.0	6.5 - 8.5	9.4	29.2	7.3	13	13.2	712	2205@50	RBL

Yokohama Tire

P235/70R17 108S	01268	XL	500/A/B	36.20	7.0	7.0 - 8.0	9.5	30.3	7.3	13	13.7	686	2205@50	OWL
245/65R17 107H	01252	SL	500/A/A	34.83	7.0	7.0 - 8.5	9.6	29.6	7.6	13	13.4	701	2149@51	RBL
255/65R17 110H	01250	SL	500/A/A	36.60	7.5	7.0 - 9.0	10.2	30.3	8.0	13	13.7	685	2337@51	RBL
P255/70R17 110S	01269	SL	500/A/B	40.10	7.5	6.5 - 8.5	10.2	31.3	8.0	13	14.1	664	2337@51	OWL
265/65R17 112H	01246	SL	500/A/A	38.14	8.0	7.5 - 9.5	10.7	30.7	8.3	13	13.9	675	2469@51	RBL
P265/70R17 113S	01237	SL	500/A/B	40.79	8.0	7.0 - 9.0	10.8	31.9	8.3	13	14.3	651	2535@51	OWL
P275/60R17 110S	01264	SL	500/A/B	43.70	8.0	7.5 - 9.5	11.1	30.1	8.6	13	13.6	690	2337@51	OWL
275/65R17 115H	01248	SL	500/A/A	41.45	8.0	7.5 - 9.5	11.0	31.3	8.6	13	14.1	664	2679@51	RBL
285/65R17 116H	01298	SL		42.60	8.5	8.0 - 10.0	11.6	31.6	9.3	14	14.2	658	2756@51	BW
225/55R18 GEOLANDAR A/T-S 98H G012	01300		500/A/A	28.50	7.0	6.0-8.0	9.1	27.8	7.3	12	12.8	748	1653@51	BW
265/60R18 110H	01270	SL	500/A/A	41.01	8.0	7.5 - 9.5	10.8	30.5	8.3	12	13.9	681	2337@51	RBL
P265/70R18 114S	01272	SL	500/A/B	41.40	8.0	7.0 - 9.0	10.8	32.8	8.3	14	14.8	663	2601@51	RBL
275/60R18 112H	01271	SL	500/A/A	41.90	8.0	7.5 - 9.5	11.1	31.0	8.6	12	14.1	669	2469@51	RBL
285/60R18 116H	01297		500/A/A	42.50	8.5	8.0 - 10.0	11.5	31.6	8.9	13	14.3	658	2756@51	BW
275/55R20 GEOLANDAR A/T-S 117S REIN.	01278	RF	500/A/B	41.25	8.5	7.5-9.5	11.0	32.0	9.0	13	14.7	648	2833@50	BW
305/45R20 112H	01242	SL	500/A/A	44.97	10	9.5 - 11.5	11.7	31.1	10.9	13	14.3	669	2469@51	RBL
LT215/75R15 100/97S (C)	01257	C		32.41	6.0	5.5 - 7.0	8.3	27.9	6.7	16	13.4	738	1765@50	OWL
LT235/75R15 104/101S (C)	01230	C		36.82	6.5	6.0 - 7.0	9.3	29.2	7.3	16	14.0	706	1985@50	OWL
LT215/85R16 110/107R (D)	01244	D		37.92	6.0	5.5 - 7.0	8.7	30.5	6.3	16	14.6	676	2335@65	OWL
LT225/75R16 110/107 (D)	01243	D		37.70	6.0	6.0 - 7.0	8.8	29.5	7.0	16	14.1	699	2335@65	OWL
LT235/85R16 120/116R (E)	01232	E		49.60	6.5	6.0 - 7.5	9.4	31.9	7.3	16	15.2	647	3042@80	OWL
LT245/75R16 120/116R (E)	01222	E		47.62	7.0	6.5 - 8.0	9.7	30.7	7.6	16	14.5	674	3042@80	OWL
LT265/75R16 119/116R (D)	01226	D		49.60	7.5	7.0 - 8.5	10.7	31.9	8.3	17	15.3	647	3000@65	OWL
LT265/75R16 123/120R (E)	01254	E		50.93	7.5	7.0 - 8.0	10.6	31.9	8.3	17	15.2	648	3415@80	RBL
LT285/75R16 122/119R (D)	01227	D		55.34	8.0	7.5 - 9.0	11.5	33.1	8.9	17	15.8	623	3305@65	RBL
LT315/75R16 121R (D)	01249	D		61.51	8.5	8.0 - 10.0	12.6	34.5	9.8	18	16.3	602	3195@50	RBL
LT235/80R17	01293	E		52.00	6.5	6.0-7.5	9.1	32.0	7.3	16	15.1	654	3085@80	BW
LT245/70R17 119/116 (E)	01251	D		46.90	7.0	6.5 - 8.0	9.6	30.8	7.6	17	14.6	673	3000@80	RBL
LT245/75R17	01295	E		44.80	7.0	6.5-7.5	9.6	31.8	7.6	17	15.0	656	3195@80	BW
LT265/70R17 121/118R (E)	01234	E		52.20	8.0	7.0 - 8.5	10.5	32.0	8.3	17	15.0	651	3195@80	RBL

LT285/70R17 121/118R	01292	D		56.20	8.5	7.5-9.0	11.3	33.1	8.9	18	15.8	629	3195@65	BW
LT315/70R17 121/118R (D)	01225	D		61.93	9.5	8.5 - 10	12.5	34.6	9.8	18	16.3	601	3195@50	RBL
LT275/65R18 113/110S (C)	01265	C		52.00	8.0	7.5 - 9.0	11.1	32.3	8.6	17	15.2	649	2535@50	OWL
LT275/65R18 123/120R	01296	E		57.00	8.0	7.5-9.0	11.0	32.4	8.6	18	15.4	644	3415@80	BW
LT285/65R18 121/118R	01301	D		54.60	8.5	8.0-10.0	11.1	32.6	8.9	17	15.3	648	3195@65	BW
LT325/60R20 121/118S	01303	D		69.40	9.5	9.0-12.0	13.0	35.7	10.6	17	17.1	581	3195@50	BW
30X9.50R15 104S (C)	01231	C		37.26	7.5	6.5 - 8.5	9.7	29.6	7.6	16	14.0	699	1985@50	OWL
31X10.50R15 109S (C)	01223	C		43.65	8.5	7.0 - 9.0	10.7	30.6	8.3	17	14.4	680	2270@50	OWL
32X11.50R15 113S (C)	01255	C		51.59	9.0	8.0 - 11.0	11.5	31.5	9.1	17	14.8	659	2535@50	OWL
33X12.50R15 108S (C)	01256	C		54.31	10.0	8.0 - 11.0	12.8	32.5	9.8	17	15.5	636	2205@35	OWL
LT37X12.50R17 124R (D)	01273	D		71.60	10.0	8.5 - 11.0	12.9	36.5	9.8	17	17.4	573	3525@50	RBL
37X12.50R18 GEOLANDAR A/T-S 123R(D)	01275	D		73.80	10.0	8.5 - 11.0	12.7	36.6	9.8	18	17.4	579	3415@50	BW
37X12.50R20 GEOLANDAR A/T-S 120R(D)	01276	D		73.30	10.0	8.5 - 11.0	12.2	36.7	9.8	18	17.5	577	3085@50	BW

